



BUILT FOR VERSATILITY

Available in two widths, LEC2-330S 762mm (30") and LEC2-640S 1625mm (64") these flatbed printers offer an impressive printable height of 200mm and weight capacity on the printing table of 100kg/m².



IMPRESSIVE PRINT CAPABILITY

Print onto a virtually limitless range of flexible and rigid substrates and objects.



TIME-SAVING TURNAROUND

Deliver a fast turnaround on jobs, with prints instantly ready for finishing and installation.



FINE PRINT QUALITY

Delight your customers with stunning quality colour-accurate prints, with ECO-UV EUV5 ink.



EASY-TO-USE

Fast-to-learn and easy-to-use, the LEC2 S-Series can be ready to use immediately after installation.



PROMOTIONAL & PERSONALISED OBJECTS



SIGN AND GRAPHICS



PACKAGING



INDUSTRIAL

Specifications

		LEC2-330S		LEC2-640S		
Model		F200 Flatbed	F200 Flatbed	F300 Flatbed	F400 Flatbed	
Printing method		Piezo ink-jet				
Acceptable media	Width	762 mm	1625 mm	1625 mm	1625 mm	
	Thickness/height	0.01 to 200mm	0.01 to 200mm	0.01 to 200mm	0.01 to 200mm	
	Weight bed	100 kg / m ²	100 kg / m ²	100 kg / m ²	100 kg / m ²	
Bed Size		820 (W) x 2085 (D) mm	1696 (W) x 2090 (D) mm	1696 (W) x 3090 (D) mm	1696 (W) x 3818 (D) mm	
Printing Size*		736 (W) x 1500 (L) x 200 (H) mm	1615 (W) x 1500 (L) x 200 (H) mm	1615 (W) x 2500 (L) x 200 (H) mm	1615 (W) x 3148 (L) x 200 (H) mm	
Ink cartridges	Type	ECO-UV EUV5				
	Colours	Cyan, Magenta, Yellow, Black, Orange, Red, White, Gloss, Primer				
Ink configurations		CMYKCMYK, CMYKWhWhGIGI, CMYKWhWhGIPr, CMYKOrReWhWh, CMYKOrReWhGI CMYKOrReWhPr				
Printing resolution (dpi)		Maximum 1440 dpi				
Movement method		High resolution stepping motor				
Dimensions	Printer unit	1945 (W) x 2152 (D) x 1780 (H) mm	2819 (W) x 2152 (D) x 1780 (H) mm	2819 (W) x 3152 (D) x 1780 (H) mm	2819 (W) x 3880 (D) x 1780 (H) mm	
	Control tower	530 (W) x 530 (D) x 1080 (H) mm				
Included accessories		RIP Software, User manual, Power cable, cleaning kit, installation toolbox				